



A-919 Boron Nitride



BORON NITRIDE

Net Quantity 500ml/300gm

DESCRIPTION: It is an insulator and white colored dry film designed for dry film lubrication on surfaces submitted to frictional contact at high temperature (>1200°C), contact with material in fusion, wear by fretting corrosion, etc,



APPLICATION: Boron Nitride aerosol may be used as a coating for: High temperature release (crucibles, molds, transition plates), High temperature lubrication, Corrosion resistance to molten metals, molten glasses and slags, Anti-oxidation barriers, Anti-stick barriers during hot pressing operations

Lubricant


Good Insulator

White colored dry film

Stable surface treatment

Ability to separate surface

INSTRUCTION: Shake very well before use. Keep the can vertically for use and storage. Spray over the surface from 30 cm distance. For best performance wait some minutes to facilitate penetration and actuation of the lubricant.



STORAGE & SHELF LIFE: Store in cool dry place away from direct sunlight. Minimum shelf life is 12 months from the date of manufacturing.

WARRANTY: Each unit is unconditionally warranted against any defect for a minimum period of 12 months from the date of supply.

FOR INDUSTRIAL USE ONLY



CAUTION

DO NOT SPRAY INTO OR AROUND OPEN FLAME & SPARK. SPRAY IN VENTILATED AREA. EXPOSURE TO HEAT OR SUNLIGHT WHERE TEMPERATURE EXCEEDS 120 F, MAY CAUSE BURSTING. DO NOT PUNCTURE OR INCINERATE CAN. STORE CAN IN COOL, DRY PLACE FOR OPTIMUM SHELF LIFE.

MANUFACTURED & MARKETING BY:-



Highly Inflammable



See bottom for
Batch No.
Mfg. Date
Exp. Date
M.R.P.
(Incl. of all taxes)

Sales & Logistic office: 105, Richa Trade Centre, Opp Nexa Show Room, above Suman Steel, Sativali Road, Vasai (E), Dist. Palgarh: 401208

Contact Board Lines: 7410006010/11/12/13/14

E-mail: sales@aarnalube.com
visit us at: www.aarnalube.com