



A-9113 FG SILICONE SPRAY



Net content 500ml / 250g

FG SILICONE SPRAY

Low evaporation

High thermal stability

Antifoaming properties

Excellent chemical stability

High resistance against oxidation

Low variation of viscosity with temperature

Best resistance against extreme temperatures

**FG SILICONE SPRAY
FOR FOOD INDUSTRY**




Nonfood Compounds
H1

DESCRIPTION: Stable to heat and high temperature resistant, silicone oil. Meet the requirements with possible accidental contact with food products.



APPLICATION: General lubrication with synthetic oils of all type of mechanisms, working at high temperatures under water influence and other contaminating products. Lubrication of mechanisms with incidental food contact, Transport belts, Guides, Machines food industry in general, De-molding of plastic operations.



INSTRUCTION: Shake very well before use. Keep the can vertically for use and storage. Spray over the surface from 30 cm distance. For best performance wait some minutes to facilitate penetration and actuation of the lubricant.

STORAGE & SHELF LIFE: Store in cool dry place away from direct sunlight. Minimum shelf life is 24 months from the date of manufacturing.

WARRANTY: Each unit is unconditionally warranted against any defect for a minimum period of 12 months from the date of supply.

CAUTION
DO NOT SPRAY INTO OR AROUND OPEN FLAME & SPARK. SPRAY IN VENTILATED AREA. EXPOSURE TO HEAT OR SUNLIGHT WHERE TEMPERATURE EXCEEDS 120 F, MAY CAUSE BURSTING. DO NOT PUNCTURE OR INCINERATE CAN. STORE CAN IN COOL, DRY PLACE FOR OPTIMUM SHELF LIFE.

MANUFACTURED & MARKETING BY:-



Sales & Logistic office: 105, Richa Trade Centre,
Opp Neha Sativali Road, Vasai (E), Dist. Palgarh:
401208105 Richa Trade Centre Opp Nexa Show Room

See bottom for
Batch No.
Mfg. Date
Exp. Date
M.R.P.
(Incl. of all taxes)

Contact Broad Lines: 7410006010/11/12/13/14
E-mail: sales@aarnalube.com
visit us at: www.aarnalube.com