

TECHNICAL DATA SHEET

MOLY SPRAY



DESCRIPTION: AARNA Moly Spray is a dry lubricant of molybdenum disulphide, appropriate for temperature up to 450°C. AARNA Moly Spray built a long life homogeneous, adherent heavy load and temperature change resistant lubricant film, Thus assuring smooth sliding and reducing the friction coefficient.

APPLICATION AREAS: spray at a distance of 10-12" from the surface for uniform layer. Shake well before use till ball moves smoothly. After each use, turn the can upside down & spray till only the propellant gas comes out.

PRECAUTIONS:

Can is under high pressure. Do not puncture or incinerate it even when apparently empty. Store below 50°C. Use in well ventilated areas. Do not spray into or around open flames and sparks. Exposure to heat, which exceeds 120°C, may cause busting of the can. Keep out of reach of children.

TECHNICAL DATA

PARAMETERS	SPECIFICATIONS
APPEARENCE	SOLID (GREYISH BLACK)
RELATIVE DENSITY	1000 g/cc
ODOUR	CHARACTERISTIC
DRYING TIME	10 MINUTE AT +25°C

STORAGE & SHELF LIFE: The product may be stored at normal ambient temperature and has a shelf life of not less 2 years with correct storage. Aerosol should always be stored below 50°C, away from direct heat and naked flame.

TECHNICAL SERVICE: AARNA LUBE PVT LTD. provides technical support under the program of research and development. For any enquiry contact us at details provided below.

Packing: - 300gm/500 ml, Aerosol Cans.

Disclaimer:

Information in this literature is to the best of our knowledge, true and accurate. However, since conditions under products may be used are beyond our control, recommendation are made without warranty or guarantee.

