

Part No.# A9111

TECHNICAL DATA SHEET

SILICON SPRAY



DESCRIPTION: Silicon Spray is a premium quality release agent based on silicon technology. It acts as general purpose lubricant where materials in contact are compatible with silicon oils. Silicon spray has an excellent surface coverage. It is non toxic with good temperature stability.

APPLICATION AREAS: Mould release agent for plastic, Rubber, Polyester, Nylon PP etc. Lubricating agent for conveyors, guides, belt, sliding, plates, table door & windows. Also applicable for high shear ranges.

PRECAUTIONS:

Can is under high pressure. Do not puncture or incinerate it even when apparently empty. Store below 50°C . Use in well ventilated areas. Do not spray into or around open flames and sparks. Exposure to heat, which exceeds 120°C, may cause busting of the can. Keep out of reach of children.

CHEMICAL AND PHYSICAL PROPERTIES

PHYSICAL STATE	LIQUID
APPEARANCE	COLOURLESS
SOLUBILITY IN H2O	INSOLUBLE
PROPELLANT GAS	LPG
ODOUR	CITRUS
FLASH POINT	-17°C
SPECIFIC GRAVITY	0.87

STORAGE & SHELF LIFE: The product may be stored at normal ambient temperature and has a shelf life of not less 2 years with correct storage. Aerosol should always be stored below 50°C, away from direct heat and naked flame.

TECHNICAL SERVICE: AARNA LUBE PVT LTD. provides technical support under the program of research and development. For any enquiry contact us at details provided below.

Packing: - 300gm/500 ml, Aerosol Cans.

Disclaimer:

Information in this literature is to the best of our knowledge, true and accurate. However, since conditions under products may be used are beyond our control, recommendation are made without warranty or guarantee.



Sales & Logistic office: 105, Richa Trade Centre, Opp Neha Sativali Road, Vasai (E), Dist. Palgarh: 401208105 Richa Trade Centre Opp Nexa Show Room

Contact Broad Lines: 7410006010/11/12/13/14, E-mail: sales@aarnalube.com

visit us at: www.aarnalube.com