

Part No.# A901

## **TECHNICAL DATA SHEET**

## **ZINC SPRAY**



**DESCRIPTION:** A unique combination of zinc powders and resins, formulated to form a high performance zinc-rich coating that actively fights rust and corrosion by its galvanic properties. Ferrous metals are protected by the sacrificial action, even when scratched or damaged. Excellent touch-up for damaged galvanized surfaces. Good mechanical resistance due to the excellent adhesion on metal.

**APPLICATION AREAS:** For general use in all situations where clean and degreased metal surfaces need to be protected against corrosion:

- Power generation equipment Trailers Transmission towers Transformers Ships
- Radio and T.V. relay towers Sub-station equipment Fencing Structural steel
- Railroad equipment Roofs Guard rails Coastal and ship borne installations Storage tanks.
- Welding seams rivet holes Off shore oil rigs Repair of galvanized parts Home, garden and farm equipment

## **PRECAUTIONS:**

Stir/Shake well before applying. Store below  $50^{\circ}\mathrm{C}$ . Use in well ventilated areas. Do not use into or around open flames and sparks. Keep out of reach of children

## CHEMICAL AND PHYSICAL PROPERTIES

PHYSICAL STATE	LIQUID
APPEARANCE	ZINC SILVER
TEMP. RANGE	UP-TO 220°C
TOUCH DRY/FULL CURE	10 Min/24 Hr
TIME TO OVER COAT	AFTER 20Min
FLASH POINT	>30°C
PURITY OF ZINC PASTE	99.8%

**STORAGE & SHELF LIFE:** The product may be stored at normal ambient temperature and has a shelf life of not less 2 years with correct storage. Should always be stored below 50°C, away from direct heat and naked flame.

**TECHNICAL SERVICE:** AARNA LUBE PVT LTD. provides technical support under the program of research and development. For any enquiry contact us at details provided below.

Packing: - 5/customized(Ltr).

Disclaimer:

Information in this literature is to the best of our knowledge, true and accurate. However, since conditions under products may be used are beyond our control, recommendation are made without warranty or guarantee.

