

TECHNICAL DATA SHEET

LEAK DETECTOR



DESCRIPTION: It is a non-toxic, non-corrosive formulation Excellently suited for locating even extremely small leaks which can be made visible by immediate formation of bubbles at leak location.

APPLICATION AREAS: Location of leaks in pressurised piping and containers, e.g. on compressors, steel bottles, fittings, shut-off valves, breathing devices, oxyacetylene gas and inert-gas arc welding devices, Bunsen burners, valves, screw fittings of compressed-air lines etc. Suitable for compressed air, refrigerant, acetylene, butane, natural gas, carbon dioxide, gaseous oxygen, propane, town gas, nitrogen, hydrogen, and ammonia

PRECAUTIONS:

Can is under high pressure. Do not puncture or incinerate it even when apparently empty. Store below 50°C . Use in well ventilated areas. Do not spray into or around open flames and sparks. Exposure to heat, which exceeds 120°C, may cause busting of the can. Keep out of reach of children.

CHEMICAL AND PHYSICAL PROPERTIES

PHYSICAL STATE	LIQUID
APPEARANCE	TRANSPARENT
SOLUBILITY IN H2O	SOLUBLE
ODOUR	CHARACTERISTIC
RELATIVE DENSITY	1

STORAGE & SHELF LIFE: The product may be stored at normal ambient temperature and has a shelf life of not less 2 years with correct storage. Aerosol should always be stored below 50°C, away from direct heat and naked flame.

TECHNICAL SERVICE: AARNA LUBE PVT LTD. provides technical support under the program of research and development. For any enquiry contact us at details provided below.

Packing: - 300gm/500 ml, Aerosol Cans.

Disclaimer:

Information in this literature is to the best of our knowledge, true and accurate. However, since conditions under products may be used are beyond our control, recommendation are made without warranty or guarantee.



