

Part No.# A9314

TECHNICAL DATA SHEET

ANTI-SEIZE SPRAY



DESCRIPTION: It is a High-temperature screw paste aerosol on copper basis for preventing corrosion, seizing and binding.

APPLICATION AREAS: Assembling screw threaded connections subjected to high temperatures and corrosive influences. Screwed connections at pipe fittings, flange joints and fittings in superheated steam lines. Combustion chamber screwed connections and mounting bolts of gas and oil burners. Screwed connections at combustion engines, exhaust systems, silencers and exhaust gas pipe connections.

PRECAUTIONS:

Can is under high pressure. Do not puncture or incinerate it even when apparently empty. Store below 50°C . Use in well ventilated areas. Do not spray into or around open flames and sparks.

TECHNICAL DATA

	Value
Application-specific data	
APPEARANCE	Metallic Grey
ODOUR	Solvent
SPECIFIC GRAVITY AT 20°C	0.8
SOLUBILITY	Insoluble in water
FLAMMABILITY	Highly Flammable
TEMPERATURE RANGE	-30 to 1100 °C

ADVANTAGES & BENIFITS

- Allows reliable non-destructive dismantling even after longer
- operating period under high operating and ambient temperatures
- Provides an optimal ratio of screw pretension and tightening torque Electrically conductive

STORAGE & SHELF LIFE: The product may be stored at normal ambient temperature and has a shelf life of not less 2 years with correct storage. Should always be stored below 50°C, away from direct heat and naked flame.

TECHNICAL SERVICE: AARNA LUBE PVT LTD. provides technical support under the program of research and development. For any enquiry contact us at details provided below.

Packing: - 500 ml..

Disclaimer:

Information in this literature is to the best of our knowledge, true and accurate. However, since conditions under products may be used are beyond our control, recommendation are made without warranty or guarantee.

