

**Industrial lubricants** 



METAL FORMING & CUTTING FLUIDS

A Global Supplier
Since 1885







# **Industrial lubricants**

SHEET STAMPING	G, METALFORM	ING AND FORMING PROCESSES
SOLUBLE PRODUCTS	FOR STEEL AND S	TAINLESS-STEEL STAMPING AND METALFORMING
PRODUCTS	VISCOSITY	DESCRIPTION
BESTRIL S	177	Stainless steel deep metalforming and stamping
EVAPORATING PROD	UCTS, CONTAIN SO	DLVENTS
PRODUCTS	VISCOSITY	DESCRIPTION
BESPURB 60	-	Aluminum stamping
BESPRUB 70	-	Aluminum stamping

COPPER WIRE DR	AWING PRODU	JCTS
PRODUCTS	VISCOSITY	DESCRIPTION
BESTRIL 230	-	Copper wire-drawing, Medium and thin wires

ALUMINIUM PROFILE CUTTING					
PRODUCTS VISCOSITY		DESCRIPTION			
BESTRIL 244	10	Cutting oil for aluminium profiles, it does not stain in the thermal treatment of aging			

ALUMINUM AND ZINC DIE CASTING					
PRODUCTS	VISCOSITY	DESCRIPTION			
BESTRIL 1290 MOD	-	Water soluble synthetic releasing fluids, parts difficult to be released			
BESTRIL 80 AG	320	Plunger lubricant, graphited			
BESTRIL FSP-320	337	Plunger lubricant without graphite			
BESTRIL FSP-1	-	Plunger lubricant, granulated wax, particle size 1 to 3 mm			

HIGH TECHNOLOGY NEAT CUTTING OILS							
MACHINING PR	ODUCTS						
PRODUCTS	VISCOSITY		MATERIAL		APPLICATION		
	cSt, 40°C	Steel	l Aluminum Brass				
BESCUT 23	18-21	>	>	>	Neat cutting oil for general machining in operations of medium severity.  Contains EP additives.		
LOW ENVIRONMENTAL IMPACT PRODUCTS							
BESCUT 148	20.5 -23	>	7	>	Neat cutting oil for High severity machining operations. Milling, turning, threading, grinding, etc.		
BESCUT 149	35 - 40	>	7	>	Neat cutting oil for High severity machining operations. Turning, gear cutting hobbing machines, etc. Contains EP additives.		
HIGH PERFORMANACE LOW ENVIRONMENTAL IMPACT PRODUCTS							
BESCUT 361	9-11	*	*		Neat cutting oil for Grinding and sharpening of hard metal tools. Special for Walter sharpening machines. High flash point, it does evaporate and it does not form mist.		



# Industrial lubricants

MQL MACHINI	ING PRODUCTS							
PRODUCTS	VISCOSITY	MAT	ERIAL		AF	PPLICATI	ION	
	cSt, 40°C	Steel Alun	ninum	Brass				
BESCUT 173	34 - 42	3 !	<b>Y</b>		Sy	nthetic fl	uid for machining by micro-pulverization & cutting.	
BESCUT 177	40 - 48	3	7		Synthetic fluid for machining by micro-pulverization and cutting with belt and circular saws at high speeds.			
BESCUT 188	30 - 35	7 ;	<b>*</b>				uid for machining operations by spraying and cutting at high severe Contains EP additives.	
SPECIAL PROI	DUCTS							
BESCUT E	2,5 - 2,7	<b>y</b>			Di	electric fl	luid for EDM operations. Special for high precision machines.	
BESCUT INOX MATIC	150	7					duct with special Extreme Pressure additives for drilling operations apping steels and stainless steels.	
PULOIL 142	4,5 - 5,5	7 ;	ð.		Po	lishing, l	apping and grinding wheel, and honing abrasive belt	
MACHINING P	RODUCTS							
PRODUCTS	WATER	EMULSION	Τ	MA	TERIAI	LS	APPLICATIONS	
	HARDNESS HF	ASPECT	Stee	el Alun	ninum	Brass		
BESAL 5	Up to 50	Milky	3	,	*	*	Mineral water emulsifiable cutting fluid. General machining. Good lubrication and anticorrosive protection	
SPECIAL PROI	DUCTS							
BESAL 355	5 - 40	Opalescent white	3	,	<b>*</b>	3	Semi synthetic bacteriostatic water emulsifiable cutting fluid.  Machining of medium severity operations. It does not ferment, thus obtaining long service life and stability.	
BESAL 455	40 - 100	Opalescent	3	,	<b>*</b>	*	Semi synthetic bacteriostatic water emulsifiable cutting fluid.  Machining of medium severity operations. It does not ferment, thus obtaining long service life and stability.	
LOW ENVIRON	NMENTAL IMPAC	T PRODUCTS						
BIOSTATIC								
SERVOL 334	3 - 50	Opalescent	3	•	¥		Semi synthetic emulsifiable cutting fluid, multifunctional, EP and biostatic. High severity machining. Particularly appropriate for high precision machining. long life expectancy.	
SERVOL 533	10 - 40	Opalescent	8	,	*		Semi -synthetic multipurpose emulsifiable cutting fluid for severe mechanization with EP aditives, boro-free and no formaldehyde released. High severity machining. Particularly designed for Mapal tools. Long life expectancy.	
SERVOL 510	Up to 30	Opalescent blue	*	,	*	>	Synthetic multipurpose emulsifiable cutting fluid for severe mechanization with EP aditives, boro-free and no formaldehyde released. High severity machining. Particularly appropriate for product unification of all materials. long life expectancy.	
SERVOL 2	10 - 100	Transparent	3	,	<b>*</b>	7	Synthetic emulsifiable cutting fluid, multifunction, stable and E.P.  Multifunctional synthetic fluid for severe operations machining and grinding and high precision finishes. Contains EP additives. Long life expectancy.	

#### CUTTING FLUIDS FOR METALWORKING

Our **BESCUT**, **SERCUT** and **PULOIL** ranges cover every need and they have a wide field of application, reducing strength and cutting temperatures. They increase cutting tools life expectancy providing an excellent surface finishing of the parts.

**SERCUT** products do not evaporate and do not form mist at the working area. They also have advantages in terms of product saving and mist removal.

**BESCUT** is our full range of pure cutting oils for all machining operations and grinding of special metals for all sorts of machines and operations.

**PULOIL** range includes special products for grinding and polishing operations which require low viscosity pure cutting oils.

#### METALFORMING

**BESTRIL** range includes neat oils and soluble oils to be used as a neat product or water emulsified in plastic forming processes of metals (with no shaving removal) such as drawing, wire drawing, calibrating and similar processes involving all kind of metals.

**BESTRIL** products guarantee higher production efficiency since fewer parts will be broken and rejected. Besides this, the working parts involved will be less affected by wear.

Brugarolas researches, develops, manufactures and supplies lubricants for various industrial activities tested by the highest quality control systems worldwide, meeting the following ISO standards: IQNET ISO 9001, ISO-TS16949.









## Industrial lubricants



#### BRUGAROLAS, S.A.

Camino de la Riera, 36-44 (P.I. Cova Solera) 08191 Rubí (Barcelona) – ESPAÑA

#### Factory

Phone +34 93 588 31 00 Fax. +34 93 588 31 01 mailbox@brugarolas.com Commercial Dept Phone +34 90 222 31 00 Fax. +34 93 697 63 01

comercial@brugarolas.com

### BRUGAROLAS, ITALIA

C. SO Filippo Turati, 11/C. TORINO - 10128 Phone: +39 -011-599114 Fax: +39-011-581 89 90 info@brugarolasitalia.it

## BRUGAROLAS Deutschland GmbH

Wameler Berg 13b 59519 Möhnesee - GERMANY Phone: +49 (0) 2924 3309934 Fax: +49 (0) 2924 3309736 info@brugarolas.de

### BRUGAROLAS FRANCE

50 rue de la Garenne, 38070 St Quentin Fallavier FRANCE

Phone: +33 (0) 4 74 95 64 12 www.brugarolas.fr

brugarolasfrance@brugarolas.com

## BRUGAROLAS INDIA PRIVATE LIMITED

105, Richa Trade centre, Sativali Road Above Mahindra showroom, Vasai - East

Dist. Palghar - 401208 (India)

Sales related queries Phone : +91 741006011 / 12 Logistics related queries Phone : +91 741006013 Accounts related queries Phone : +91 741006014

info@brugarolasindia.com www.brugarolas.com